




SK 500

RF Wireless Systems | evolution wireless 

Cat. No. 021632

General Description


Designed for professional applications, the extremely compact SK 500  bodypack transmitter is an ideal match for the ew 500  Series receivers and the EM 550 . The transmitter features nine frequency banks with up to 20 directly accessible pre-sets each – ready for immediate use.



Technical Data

RF frequency range	518–866 MHz
Transmission frequencies	1,440
Presets.....	max. 20
Switching bandwidth.....	36
Peak deviation.....	± 48 kHz
Compander	HDX
AF frequency response.....	40–18,000 Hz
Signal-to-noise ratio.....	> 115 dB(A)
THD.....	< 0.9 %
In compliance with.....	ETS 300422, ETS 300445, CE, FCC
Audio connector.....	3.5 mm jack
Power supply	2 x 1.5 V (AA)
RF output power	30 mW
Operating time.....	> 8 hrs
Input voltage range	mic 1.8 V, line 2.4 V
Dimensions	82 x 64 x 24 mm
Weight	158 g






Features

- Absolutely reliable transmission and extended range due to high RF output power
- Pilot tone squelch for eliminating RF interference
- Rugged metal housing
- Contacts for recharging the BA 2015 accupack directly in the transmitter
- Backlit display (lights up when a button is pushed)
- Lock function avoids accidental changing of settings
- HDX compander for crystal-clear sound
- 4-step battery status display, also transmitted to receiver
- Mute function
- Wide range of accessories adapts the transmitter to any requirement
- Delivery includes: 1 SK 500  bodypack transmitter
 - 1 protective pouch
 - 2 batteries

Recommended Accessories

- | | |
|--|-----------------|
| ■ MKE 2-EW GOLD clip-on microphone | Cat. No. 009831 |
| ■ MKE 2-EW-3 GOLD clip-on microphone | Cat. No. 009832 |
| ■ ME 2-N clip-on microphone (omni-directional) | Cat. No. 005018 |
| ■ ME 4-N clip-on microphone (cardioid) | Cat. No. 005020 |
| ■ ME 3-N headmic (super-cardioid) | Cat. No. 005019 |
| ■ CI 1-N guitar cable | Cat. No. 005021 |
| ■ CL 2 line cable, connector: XLR-3, female | Cat. No. 004840 |

Product Variants

- | | |
|--|-----------------|
| ■ SK 500  -A: Frequency range 518–554 MHz | Cat. No. 009762 |
| ■ SK 500  -B: Frequency range 626–662 MHz | Cat. No. 009778 |
| ■ SK 500  -C: Frequency range 740–776 MHz | Cat. No. 009764 |
| ■ SK 500  -D: Frequency range 786–822 MHz | Cat. No. 009765 |
| ■ SK 500  -E: Frequency range 830–866 MHz | Cat. No. 009766 |